

# Checklist Control Valve

## Your RFQ:

Send checklist to: [sales@stoehr-valves.de](mailto:sales@stoehr-valves.de)

### Valve type, sizes and quantity

Quantity\*:  pieces

Kind of actuation\*:  pneumatic  electric  solenoid

Valve type\*:  series

Body type\*:  angle (90°)  straight-through (180°)

Nominal diameter\*:  DN

Nominal pressure:  PN minimal  PN normal  PN maximum\*

Type of medium or combination of medias\*:  e.g. He

Medium temperature\*:  temp.  °C  K

Required connections:  type  measurement  standard

### Further options

Welding flange for vacuum-jacketing\*:  yes

Surface treatment:  polished  electro polished

Purge connections:  yes

Purge valve:  yes

Thermal coupling:  copper flange  sliding thermal contact

Customer specific acceptance tests:  please specify

### Supplementary information

Expected heat input:  Watt

Temperature installation area:  °C

### Actuator

In case of pneumatic actuator, how much service pressure is given?  bar  6 bar

Fail safe position\*:  none  NO  NC

ATEX:  yes

Mounting parts\*:  pilot valve  limit switches  IP regulator  
 air pressure reducer  air filter

### Regulation

Required flow rate:  Kv- /Cv-Wert

Required control characteristic:  equal percentage

### 7. Sender

Company, Institute\*:

Contact name:

Phone\*:

Email\*:

Signature:

\* = mandatory | blue = standard