

Checklist Globe Valve: pneumatic, electric, solenoid

Your RFQ:

Send checklist to: sales@stoehr-valves.de

Valve type, sizes and quantity

Quantity*: pieces

Kind of actuation*: pneumatic electric solenoid

Valve type*: series

Body type*: angle (90°) straight-through (180°)

Nominal diameter*: DN

Nominal pressure: PN minimal PN normal PN maximum*

Type of medium or combination of medias*: e.g. He

Medium temperature*: temp. °C K

Required connections: type measurement standard

Supplementary information

Expected heat input: Watt

Temperature installation area: °C

Location of installation: indoor outdoor

Special requirements: desert, salty water etc.

Installation position: optional normal

Others: closing time opening time min. hubs

Actuator

In case of pneumatic actuator,
how much service pressure is given? bar 6 bar

In case of electrical power,
which voltage and type is required? Volt type of voltage

Fail safe position*: none NO NC

ATEX: yes

Mounting parts*: pilot valve limit switches
 air pressure reducer air filter

Further options

Welding flange for vacuum-jacketing*: yes

Surface treatment: polished electro polished

Purge connections: yes

Purge valve: yes

Customer specific acceptance tests: please specify

Sender

Company, Institute*:

Contact name:

Phone*:

Email*:

Signature:

* = mandatory | blue = standard